

# IZUHAN<sup>®</sup>

## Products catalogue



IZUHAN<sup>®</sup>

nexler<sup>®</sup>

izolmat

IZOLEX<sup>®</sup>

# IZOHAN®

Professional  
Waterproofing  
Systems

together 30 years



Izohan is a Polish, dynamically developing company set up in 1989. By introducing modern technologies and solutions it has become a market expert in waterproofing and construction chemicals.

Since 2006 the company has been working within the structure of the Atlas Group. Currently it unites five brands: **IZOHAN, IZOLEX, IZOLMAT, NEXLER** and **IZOLMIX**. Izohan brings the widest range of construction chemicals and waterproofing products available on the market, it offers hundreds of system solutions supporting the contractors at any stage of the investment process.

Izohan offers, i.a. sealing micro-mortars, epoxy materials, bitumen masses, PCC mortars, impregnants, products for renovation and fumigation, polyurethane foams, PVC membranes, shingles and bitumen roll materials.

Izohan is a modern company assuring repetitiveness of the processes as well as the highest quality products confirmed by numerous trade and industrial awards and prizes.

*Izohan products  
build the world around us!*



Consumer Quality Leader



Building Company of the Year



Construction Designer of the Year



Pomeranian Employer of the Year



Gold Emblems QI



Golden Payer Certificate



Fair Play Company



Forbes Diamond

### products DYSPERBIT

- 06 IZOHAN DYSPERBIT
- 06 IZOHAN DYSPERBIT premium ROOF
- 06 IZOHAN DYSPERBIT premium FOUNDATION
- 06 IZOHAN DYSPERBIT premium PRIMER

### water-based bitumens

- 07 IZOHAN WL
- 07 IZOHAN WK
- 07 IZOHAN WK plus
- 07 IZOHAN WM
- 08 IZOHAN WM 2K
- 08 IZOHAN WM 2K plus
- 08 IZOHAN WB
- 08 IZOHAN WA

### solvent-based bitumens

- 09 IZOHAN PENETRATOR G7
- 09 IZOHAN Br
- 09 IZOHAN SBS-Br
- 09 IZOHAN B
- 10 IZOHAN SBS-B
- 10 IZOHAN Gr
- 10 IZOHAN SBS-Gr
- 10 IZOHAN STYROTEx
- 11 IZOHAN SBS-tixo
- 11 IZOHAN Br-tixo
- 11 IZOHAN R
- 11 IZOHAN filling mass
- 12 IZOHAN ROOFIX
- 12 IZOHAN IMS
- 12 IZOHAN epoxy X9

### mineral-polymer products

- 13 IZOHAN priming solution
- 13 IZOHAN EKOLEP
- 13 IZOHAN EKO 1K
- 13 IZOHAN EKO 2K
- 14 IZOHAN CRISTALIZATOR K6
- 14 IZOHAN ECO-FOIL
- 14 IZOHAN watertight bathroom
- 14 IZOHAN watertight foundation
- 15 IZOHAN watertight terrasse
- 15 IZOHAN epoxy C-505
- 15 IZOHAN epoxy C-506

### restoration and mould removal

- 16 IZOHAN protect fungi
- 16 IZOHAN stop fungi
- 16 IZOHAN waterproofing emulsion
- 16 IZOHAN waterproofing paint

### polyurethane foams

- 17 IZOHAN styropuk foundation
- 17 IZOHAN styropuk facade
- 17 IZOHAN styropuk roof
- 17 IZOHAN foam cleaner

### adhesives and sealants

- 18 IZOHAN LIQUID GLASS
- 18 IZOHAN FULL-FIX
- 18 IZOHAN ELASTIC
- 18 IZOHAN FAST&Strong
- 19 IZOHAN premium glue for bitumen membranes and shingles
- 19 IZOHAN roofing adhesive
- 19 IZOHAN roofing sealant
- 19 IZOHAN bituminous roofing sealant
- 20 IZOHAN roofing putty

### impregnates and coatings

- 20 IZOHAN IZO-DEKOR
- 20 IZOHAN impregnant IPC
- 20 IZOHAN impregnant W2
- 21 IZOHAN PAVEMENT GUARD
- 21 IZOHAN epoxy P-405
- 21 IZOHAN epoxy EP-601
- 21 IZOHAN epoxy EP-602
- 22 IZOHAN epoxy EP-603 horizontal
- 22 IZOHAN epoxy EP-603 vertical
- 22 IZOHAN SEPARATOR B

### concrete repair and protection

- 23 IZOHAN renobud R-102
- 23 IZOHAN renobud R-103
- 23 IZOHAN renobud R-105
- 23 IZOHAN renobud R-112
- 24 IZOHAN renobud R-120
- 24 IZOHAN renobud R-140
- 24 IZOHAN sealing compound for hot application

## IZOLEX®

### products DYSPERBIT

- 25 IZOLEX DYSPERBIT GRUNT primer
- 25 IZOLEX DYSPERBIT Dn

### water-based bitumens

- 25 IZOLEX STYRBIT 2000
- 25 IZOLEX HYDROLEX 2E
- 26 IZOLEX HYDROLEX 2E STYRO

### solvent-based bitumens

- 26 IZOLEX ARBOLEX AQUA STOP
- 26 IZOLEX STYRBIT 2000-K
- 26 IZOLEX IZOBIT Br
- 27 IZOLEX IZOBIT Dk
- 27 IZOLEX COLD-APPLIED BINDER
- 27 IZOLEX IZOBIT ALU

### mineral-polymer products

- 28 IZOLEX IZOFOL
- 28 IZOLEX IZOFOL FLEX
- 28 IZOLEX IZOFOL ROOF
- 28 IZOLEX CEMIZOL 2EP
- 29 IZOLEX CEMIZOL HSR
- 29 IZOLEX GRUNTOFOL





## heat-welded top membranes

- 30 IZOLMAT PLAN monomax®
- 30 IZOLMAT PLAN protection® PYE PV250 55,2 55
- 30 IZOLMAT PLAN PYE PV250 55,2 55
- 31 IZOLMAT PLAN extra PYE PV200 55,2 55
- 31 IZOLMAT PLAN PYE PV200 54,2 55
- 31 IZOLMAT opti 20 PYE PV250 55,2 55
- 32 IZOLMAT BIT V60 54,2 55

## heat-welded underlayer membranes

- 32 IZOLMAT PLAN PYE PV250 55,0
- 32 IZOLMAT PLAN PYE G200 54,0
- 32 IZOLMAT PLAN PYE PVI80 54,0
- 33 IZOLMAT PLAN ultimax
- 33 IZOLMAT PLAN ultimax SBS
- 33 IZOLMAT PLAN PYE PVI60 53,0
- 33 IZOLMAT opti 20 PYE PV200 54,0
- 34 IZOLMAT opti 5 PYE PV200 54,0
- 34 IZOLMAT opti 5 PYE G200 54,0
- 34 IZOLMAT BIT G200 54,0
- 34 IZOLMAT BIT V60 54,0
- 35 IZOLMAT BIT V60 53,0

## special membranes

- 35 IZOLMAT TOP SP
- 35 IZOLPLAN PYE G200 53,0 SP
- 35 IZOLMAT PLAN green roof PYE PV250 55,0
- 36 IZOLMAT PLAN green roof PYE PV200 54,2
- 36 IZOLPLAN membrane® SP
- 36 IZOLMAT PLAN aquastoper® AI (SP)
- 36 IZOLMAT PLAN optimax® PV
- 37 IZOLVENT
- 37 IZOLMAT V60 54,0 AI
- 37 IZOLMAT THERMOSTICK

## traditional membranes

- 37 W/400/1200
- 38 P333-I
- 38 I-333
- 38 P/64/1200
- 38 P/100/1200F

## BITUMEN SHINGLES

- 39 Bitumen shingles



## heat-welded top membranes

- 42 NEXLER PREMIUM ONE (PYE PV250 553)
- 42 NEXLER PREMIUM 56H (PYE PV250 556)
- 42 NEXLER PREMIUM 53H (PYE PV250553)
- 42 NEXLER PJ 53 H
- 43 NEXLER PJ 52 H
- 43 NEXLER PJ 52 H Medium
- 43 NEXLER STANDARD 42H (V60 542)

## traditional membranes

- 43 NEXLER W400

## heat-welded underlayer membranes

- 44 NEXLER PREMIUM 47 (PYE PV250 547)
- 44 NEXLER PREMIUM 40 (PYE PV200 540)
- 44 NEXLER PREMIUM 29 (PYE PVI80 529)
- 44 NEXLER PJ G40 Medium
- 45 NEXLER PJ 40
- 45 NEXLER STANDARD 30 (V60 530)

## special membranes

- 45 NEXLER BRIDGE+
- 45 NEXLER STICK
- 45 NEXLER RENOVATION

## supplementary products

- 48 IZOHAN RR
- 48 BITUMEN MEMBRANE GRANULATE
- 48 HOT BINDER
- 48 ROOF-TAPE
- 49 IZOHAN BACKER ROD
- 49 IZOHAN WATERTIGHT TAPE
- 49 IZOHAN SEALING TAPE
- 49 IZOHAN butyl TAPE
- 50 IZOHAN TB 10
- 50 IZOHAN TB 20
- 50 IZOHAN TB 20
- 50 IZOHAN TB 40



Available packages:



## IZOHAN DYSPERBIT

### dispersion asphalt-rubber mass, Dn

► **Use:** renovation and conservation of roofing coatings; damp proofing; execution of jointless roofing coatings reinforced with technical fabrics; execution of jointless roofing coatings on base coat underlay made of single roofing membrane layer; priming mineral substrates beneath main insulation after diluting with water in 1:1 ratio.

► **Properties:** easy and quick in use [ready-to-use]; can be used on dry and damp substrates; very good adhesion to mineral substrates and roofing membranes; with thixotropic properties; solvent-free; watertight; resistant to atmospheric factors.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	priming 0.2 kg/m <sup>2</sup> damp proofing 1.5 kg/m <sup>2</sup> /mm roofing coatings 0.5 kg/m <sup>2</sup> per coat
Temperature of use	from +5°C up to +25°C (product and substrate)
Technological break between application of subsequent coats	approx. 5 h
Technical Approval	IBDiM AT/2005-03-1953/3
In compliance with	PN-B-24000



Available packages:



## IZOHAN DYSPERBIT premium ROOF

### Dispersion asphalt mix for restoration and insulation of roofing

► **Use:** restoration and maintenance of roofing; jointless roofing reinforced with technical textiles; jointless roofing on underlay made of single layer membrane; priming mineral substrates for proper insulation after dilution with water at 1:1 ratio.

► **Properties:** characterised by very good adhesion to mineral substrates and roofing membrane; may be used on dry or wet substrate; exerts thixotropic properties; cold application [allows execution of works without the use of open flame], solvent-free [safe upon contact with polystyrene]; forms a uniform, elastic coating; resistant to weather conditions.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	approx. 0.3 kg/m <sup>2</sup> for priming; approx. 0.5 kg/m <sup>2</sup> /layer for roofing membrane maintenance; approx. 1.5 kg/m <sup>2</sup> /mm for technical textiles blending
Temperature of use	from +5°C to +25°C
Resistance to rain	after approx. 5 h
Compliance with standard	PN-B-24000:1997



Available packages:



## IZOHAN DYSPERBIT premium FOUNDATION

### Dispersion mix for insulation and insulating panels attachment

► **Use:** seamfree damp-proof and waterproof coatings [medium type] in the underground and ground parts of the building; [EPS and XPS]; insulation for floors in basements and garages, for insulating foundation, for adhering insulation board.

► **Properties:** has excellent adhesive properties and excellent adhesion to mineral substrates both dry and wet; quick and easy application [ready-to-use]; solvent-free [safe in contact with polystyrene]; reduces the number of operations in the performance of damp proofing course, highly-modified with rubber; has thixotropic properties, resistant to aggressive substances in the ground.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	approx. 1.5 kg/m <sup>2</sup> /mm in the performance, 4.5 kg/m <sup>2</sup> in insulating boards bonding
Temperature of use	from +5°C to +25°C
Resistance to rain	after approx. 3 h
Compliance with standard	PN-B-24000:1997



Available packages:



## IZOHAN DYSPERBIT premium PRIMER

### Fast-drying primer for hard-absorbing substrates

► **Use:** priming of mineral substrates prior to application of the actual insulation upon dilution with water at 1:2 ratio [water:DYSPERBIT premium PRIMER] for non-absorbent substrates, so-called waterproof concretes; priming mineral substrates prior to the application of the proper insulation upon dilution with water at 1:1 ratio [water:DYSPERBIT premium PRIMER] for absorbent substrates.

► **Properties:** very good adhesion to absorbent and non-absorbent substrates; can be used on a dry or wet substrate; dries quickly; quick and easy application [ready-to-use]; solvent-free [safe in contact with polystyrene]; resistant to weather conditions.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	approx. 0.2 kg/m <sup>2</sup> concentrate
Temperature of use	od +5°C do +25°C
Resistance to rain	after approx. 3 h
Compliance with standard	PN-B-24002:1997/Apt:2001

## IZOHAN WL

### dispersion asphalt-rubber mass, Dn



Available packages:



- ▶ **Use:** fixing hard polystyrene boards (EPS); priming mineral substrates beneath main insulation in IZOHAN W system (after diluting with water in 1:1 ratio); execution of jointless damp proofing of underground building elements.
- ▶ **Properties:** very good fixing properties and adhesion to mineral substrates; easy and quick in use (ready-to-use); can be applied with a paint brush, a float or a roofing brush; solvent-free; watertight; forms insulation resistant to atmospheric factors.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	priming 0.2 kg/m <sup>2</sup> damp proofing 0.6 - 0.8 kg/m <sup>2</sup> per coat EPS fixing 1.0 - 1.5 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time/ resistance to rain	up to 6 h/after 6 h
Technical Approval	IBDIM AT/2005-03-1953/3
In compliance with	PN-B-24000

## IZOHAN WK

### dispersion waterproofing and adhesive mass, Dn



Available packages:



- ▶ **Use:** fixing EPS and XPS boards onto non-absorptive substrates (sheet), absorptive ones (concrete) and polystyrene boards between themselves; fixing one- and two-side bitumen-laminated polystyrene boards and asphalt membranes to concrete substrates and between themselves in multi-layer waterproofing; execution of waterproofing coats; fixing membranes to polystyrene; fixing hard mineral wool panels.
- ▶ **Properties:** very good fixing properties; very good adhesion to concrete substrates, sheet, roofing membranes, etc.; solvent-free; watertight; easy and quick in use (ready-to-use); can be applied with a float or a spatula.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	0.8-1.3 kg/m <sup>2</sup>
Temperature of use	from +10°C up to +25°C
Coat forming time	up to 6 h
Strength peeling membrane from polystyrene	no less than 17 N
In compliance with	PN-B-24000

## IZOHAN WK plus

### two-component dispersion asphalt-rubber mass, Dn-type



Available packages:



- ▶ **Use:** fixing EPS and XPS boards onto non-absorptive substrates (sheet, membrane), absorptive ones (concrete) and polystyrene boards between themselves; fixing one- and two-side bitumen-laminated polystyrene boards; fixing roofing membranes to polystyrene; fixing asphalt membranes to concrete substrates and between themselves in multi-layer waterproofing coats; fixing hard mineral wool panels; execution of waterproofing coats.
- ▶ **Properties:** gets adhesion properties in short time; perfect fixing properties; very good adhesion to absorptive and non-absorptive substrates; solvent-free (safe in contact with insulating boards of any type); easy and quick in use; can be applied with a float or a spatula.



Composition	component A: water dispersion of asphalts, rubbers and improvers component B: mineral filler
Consumption	0.8-1.3 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Coat forming time	up to 6 h
Strength peeling membrane from polystyrene	approx. 18 N

## IZOHAN WM

### one-component dispersion waterproofing mass, KMB-type (thick coat), Bn



Available packages:



- ▶ **Use:** execution of main, jointless waterproofing of vertical and horizontal underground and ground level building elements of any type (foundation walls, basement walls, foundation slabs); fixing hard polystyrene boards (EPS); execution of vapour barrier (terraces, flat roofs); insulation of floors based on the ground; insulation of reversed terraces with IZOHAN EKO 2K.
- ▶ **Properties:** easy and quick in use (ready-to-use); does not require reinforcing insertions and leveling plaster; forms coatings of sufficient hardness and high elasticity; solvent-free; coats cracks; reinforced with microfibers; can be used on any mineral substrates; resistant to high water pressure (up to 0.8 MPa); can be used on dry and slightly damp substrates; resistant to aggressive substances commonly met in the ground acc. to PN-EN 206-1; safe in contact with polystyrene.



Composition	water dispersion of asphalts, fillers, rubbers and improvers
Consumption	1.5 kg/m <sup>2</sup> /mm
Temperature of use	from +5°C up to +25°C
Coat forming time / resistance to rain	up to 4 h (for coat 1 mm thick) / after 12 h
Technical Approval	IBDIM AT/2005-03-1953/3
In compliance with	PN-EN-15814



Available packages:



## IZOHAN WM 2K

two-component waterproofing dispersion, KMB-type (thick coat), Bn

- ▶ **Use:** insulation and protection of buildings and building elements located below the ground level against ground damp, pressureless water and water under pressure; execution of vapour barrier (terraces, flat roofs); insulation of floors based on the ground; insulation of reversed terraces with IZOCHAN EKO 2K.
- ▶ **Properties:** dry component accelerates binding; resistant to high water pressure (up to 0.8 MPa); forms coatings of sufficient hardness and high elasticity; solvent-free; can be used on any mineral substrates; coats cracks; can be used on dry and slightly damp substrates; easy and quick in use; resistant to aggressive substances commonly met in the ground acc. to PN-EN 206-1.



Composition	water dispersion of asphalts and rubbers with mineral filler
Consumption	1,2-1,3 kg/m <sup>2</sup> /mm
Temperature of use	from +5°C up to +25°C
Coat forming time / resistance to rain	approx. 4 h / after 2 h
Technical Approval	IBDiM AT/2011-02-2728/1
In compliance with	PN-EN-15814



Available packages:



## IZOHAN WM 2K plus

two-component waterproofing dispersion with polystyrene filling, KMB-type (thick coat), Bn

- ▶ **Use:** insulation and protection of buildings and building elements located below the ground level against ground damp, pressureless water and water under pressure.
- ▶ **Properties:** does not require reinforcing insertions and leveling plaster; resistant to high water pressure (up to 0.8 MPa); forms coatings of sufficient hardness and high elasticity; solvent-free; easy and quick in use; can be used on any mineral substrates; coats cracks; can be used on dry and slightly damp substrates; resistant to aggressive substances commonly met in the ground acc. to PN-EN 206-1.



Composition	water dispersion of asphalts and rubbers with polystyrene filler, mineral fillers
Consumption	1,1-1,3 l/m <sup>2</sup> /mm
Temperature of use	from +5°C up to +25°C
Coat forming time / resistance to rain	approx. 4 h / after 3 h
In compliance with	PN-EN-15814



Available packages:



## IZOHAN WB

dispersion asphalt-rubber mass, Dn

- ▶ **Use:** renovation and conservation of roofing coatings; reconstruction of membrane granules.
- ▶ **Properties:** regenerates and conserves roofing membranes; can be used on dry and damp substrate; with thixotropic properties; solvent-free; forms insulation resistant to atmospheric factors; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	0,25-0,50 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +30°C
Technological break between application of subsequent coats	min. 5 h
Drying time	approx. 5 h
In compliance with	PN-B-24000



Available packages:



## IZOHAN WA

waterborne asphalt-rubber emulsion

- ▶ **Use:** priming mineral substrates beneath main insulation after diluting with water in 1:2 ratio (water: IZOCHAN WA) for non-absorptive substrates; priming mineral substrates beneath main insulation after diluting with water in 1:1 ratio (water: IZOCHAN WA) for absorptive substrates; execution of damp proofing coats.
- ▶ **Properties:** very good adhesion to non-absorptive and absorptive substrates; can be used on dry and damp substrate; easy and quick in use; solvent-free (safe in contact with polystyrene); watertight; resistant to atmospheric factors.



Composition	water dispersion of asphalts, rubbers and improvers
Consumption	priming: 0,2 kg/m <sup>2</sup> damp proofing: 1,5 kg/m <sup>2</sup> /mm
Temperature of use	from +5°C up to +25°C
Technological break between application of subsequent coats	min. 5 h
Drying time	< 6 h
In compliance with	PN-B-24002





Available packages:



## IZOHAN PENETRATOR G7

### SBS-modified fast-drying priming solution

- ▶ **Use:** priming substrates beneath asphalt and asphalt-polymer membranes, heat-welded and self-adhesive ones; particularly useful for priming substrates beneath modified membranes; when applied in multiple coats can be used as damp proofing and protection of earth-sheltered wooden and metal elements.
- ▶ **Properties:** SBS-modified; fast-drying; perfect penetration into insulated surfaces; protects concrete against damp and corrosion; very good adhesion to mineral substrates; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush.



Composition	mix of asphalts, solvents, fillers, SBS and other improvers
Consumption	approx. 0.2 l/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	up to 30 min.
Technical Approval	IBDIM AT/2013-02-3022
In compliance with	PN-B-24620



Available packages:



## IZOHAN Br

### asphalt-resin priming solution

- ▶ **Use:** priming mineral and bitumen substrates made of asphalt membranes before application of the main asphalt insulation; application of anticorrosion coatings; conservation of corroded concrete surfaces (limits further concrete corrosion process).
- ▶ **Properties:** watertight; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush; improves substrate adhesion; perfect penetration into insulated surfaces; protects concrete against damp and corrosion; very good adhesion to any mineral substrates.



Composition	mix of asphalts, solvents and improvers
Consumption	approx. 0.3 l/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	up to 12 h
Technical Approval	IBDIM AT/2015-02-3187
In compliance with	PN-B-24620



Available packages:



## IZOHAN SBS-Br

### SBS-modified asphalt-resin priming solution

- ▶ **Use:** priming mineral and old coatings made of asphalt membranes before application of the main asphalt insulation; application of anticorrosion coatings, also on metal elements; conservation of corroded concrete surfaces (limits further concrete corrosion process).
- ▶ **Properties:** SBS-modified; perfect penetration into insulated surfaces; very good adhesion to mineral substrates; improves the substrates adhesion; forms coating resistant to atmospheric factors; protects concrete against damp and corrosion; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush.



Composition	mix of asphalts, solvents, SBS and other improvers
Consumption	approx. 0.3 l/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	up to 12 h
Technical Approval	IBDIM AT/2015-02-3187
In compliance with	PN-B-24620



Available packages:



## IZOHAN B

### asphalt-resin mass

- ▶ **Use:** conservation and renovation of roofing membranes.
- ▶ **Properties:** watertight; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush; perfect penetration into insulated surfaces; forms coating resistant to atmospheric factors; regenerates and conserves asphalt roofing membranes.



Composition	mix of asphalts, solvents, fillers and improvers
Consumption	approx. 0.5 l/m <sup>2</sup> per coat
Temperature of use	from +5°C up to +25°C
Drying time	approx. 24 h
In compliance with	PN-B-24620



Available packages:



## IZOHAN SBS-B

### SBS-modified asphalt renovating mass

- ▶ **Use:** conservation and renovation of roofing membranes.
- ▶ **Properties:** SBS-modified; regenerates and conserves asphalt roofing membranes; forms coating resistant to atmospheric factors; keeps properties both in low and high temperature; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush.



Composition	mix of asphalts, solvents, fillers, SBS and other improvers
Consumption	approx. 0.4-0.6 l/m <sup>2</sup> depending on the substrate condition
Temperature of use	from +5°C up to +25°C
Drying time	approx. 24 h
In compliance with	PN-B-24620



Available packages:



## IZOHAN Gr

### asphalt-polymer-resin coat

- ▶ **Use:** damp proofing of underground and ground level building elements in general and communication construction.
- ▶ **Properties:** watertight; easy and quick in use (ready-to-use); can be applied with a roofing brush; forms coating resistant to atmospheric factors; very good adhesion to concrete and brick.



Composition	mix of asphalts, resins, polymers, organic solvents, fillers and improvers
Consumption	approx. 0.7 l/m <sup>2</sup> /per coat
Temperature of use	from +5°C up to +25°C
Drying time	approx. 24 h
Technical Approval	IBDiM RT/2011-02-0080/1
In compliance with	PN-B-24620



Available packages:



## IZOHAN SBS-Gr

### SBS-modified, asphalt-polymer-resin coat

- ▶ **Use:** damp proofing of underground and ground level building elements in general and communication construction.
- ▶ **Properties:** SBS-modified; very good adhesion to any mineral substrates; forms coating resistant to atmospheric factors; watertight; easy and quick in use (ready-to-use); can be applied with a roofing brush.



Composition	mix of asphalts, resins, polymers, organic solvents, fillers, SBS and other improvers
Consumption	approx. 0.7 kg/m <sup>2</sup> /per coat
Temperature of use	from +5°C up to +25°C
Drying time	approx. 24 h
Technical Approval	IBDiM RT/2011-02-0080/1
In compliance with	PN-B-24620



Available packages:



## IZOHAN STYROTEx

### SBS-modified, cold application adhesive

- ▶ **Use:** fixing roofing polystyrene boards (EPS), XPS boards as well as foam glass onto concrete, trapezoid sheet and existing membrane; adhering roofing asphalt membrane layers in multi-layer roofing; fixing one- and two-side bitumen-laminated thermal insulation boards onto mineral and bitumen substrates.
- ▶ **Properties:** SBS-modified; easy and quick in use (ready-to-use); can be applied with a float or a trowel; perfect adhesion properties; resistant to atmospheric factors, low and high temperature; particularly resistant to short and long term weathering; very good adhesion to mineral substrates, membranes and sheet.



Composition	mix of asphalts, dearomatized solvents, fillers, SBS and other improvers
Consumption	approx. 0.5 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	approx. 5 h
Adhesion ability - membrane to membrane	245 ± 11 N
In compliance with	PN-B-24620

## IZOHAN SBS-tixo

### SBS-modified asphalt-resin adhesive



Available packages:



► **Use:** fixing asphalt roofing membranes onto primed concrete substrates; adhering roofing asphalt membrane layers in multi-layer insulation; execution of damp proof, jointless building insulation in IZOHAN system; fixing mineral wool panels in flat roof thermal insulation.

► **Properties:** SBS-modified; easy and quick in use (ready-to-use); can be applied with a float or a roofing brush; perfect adhesion properties; resistant to atmospheric factors, low and high temperature; particularly resistant to short and long term weathering; very good adhesion to mineral substrates and membranes.



Composition	mix of asphalts, solvents, fillers, SBS and other improvers
Consumption	approx. 0.7 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	approx. 24 h
Adhesion ability – membrane with membrane	260 ± 11 N
In compliance with	PN-B-24620

## IZOHAN Br-tixo

### asphalt-resin adhesive



Available packages:



► **Use:** fixing asphalt roofing membranes onto primed concrete substrates; adhering roofing asphalt membrane layers in multi-layer insulation; fixing mineral wool panels in flat roof thermal insulation; execution of damp proof, jointless building insulation in IZOHAN system.

► **Properties:** easy and quick in use (ready-to-use); can be applied with a float or a roofing brush; perfect adhesion properties; forms insulation resistant to atmospheric factors; very good adhesion to primed mineral substrates and roofing membranes.



Composition	mix of asphalts, solvents, fillers and improvers
Consumption	approx. 0.7 l/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	approx. 24 h
In compliance with	PN-B-24620

## IZOHAN R

### insulating and decorative coating



Available packages:



► **Use:** outdoor execution of insulating and decorative silver colour coatings; onto asphalt roofing membranes; onto bitumen roofing shingles; for eternit sealing; for conservation of zinc coated sheet elements.

► **Properties:** watertight; easy and quick in use (ready-to-use); can be applied with a paint brush or a roofing brush; very good coating properties; reflects UV rays – reduces temperature in rooms beneath; forms silver colour coating resistant to atmospheric factors; very good adhesion to sheet, concrete and membranes.



Composition	mix of asphalts, polymers and aluminum flake-like pigments
Consumption	0,15-0,3 l/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	approx. 2 h
Technical Approval	IBDIM R1/2011-02-0080/1
In compliance with	PN-B-2404 ([1997/A], [2004])

## IZOHAN filling mass

### filling mass



Available packages:



► **Use:** supplementary material for vertical damp proofing of walls and foundations with IZOHAN system; filling gaps in roofing membranes; repairs of mechanically damaged substrates previously coated with damp proofing masses IZOHAN B, IZOHAN SBS-B; flashings sealing.

► **Properties:** forms coating of sufficient hardness and high elasticity; easy and quick in use (ready-to-use).



Composition	insulating asphalts, additives
Consumption	ok. 0.9 kg/m <sup>2</sup> /mm
Temperature of use	from +5°C up to +25°C
Drying time	approx. 10 h
In compliance with	PN-B-24620



Available packages:



## IZOHAN ROOFIX

### roofing filling and repair mastic

- **Use:** filling and refilling gaps, repairs of roofing membranes (cracks, irregularities, blisters, leakages); supplementary material for vertical damp proofing of foundations with IZOCHAN system (e.g. for sealing any installation passes); flashing sealing and fixing; repairs of mechanically damaged substrates previously coated with damp proofing masses IZOCHAN B or IZOCHAN SBS-B.
- **Properties:** owing to special chemical additives can be applied onto damp and wet substrates; addition of reinforcing fibres enables to reduce significant substrate moves; can be applied even during rain; can be used in contact with polystyrene; easy and quick in use (ready-to-use).



Composition	insulating asphalts, deaerated solvents, improvers
Consumption	approx. 0.9 kg/m <sup>2</sup> /mm
Substrate and ambient temperature during application and bonding	from -20°C up to +35°C
Technological break between application of subsequent coats	min. 5 h
Drying time	approx. 10 h
In compliance with	PN-B-24620



Available packages:



## IZOHAN IMS

### KMB-type solvent damp proofing (thick-coat)

- **Use:** execution of main jointless vertical and horizontal damp proofing of any type with no reinforcing inserts.
- **Properties:** does not require leveling plasters; resistant to high water pressure (up to 0.8 MPa); forms coatings of sufficient hardness and high elasticity; easy and quick in use (ready-to-use).



Composition	asphalts modified with polymers, reinforcing fibres, organic solvents
Consumption	0.9 – 1.0 kg/m <sup>2</sup> /mm of coat
Temperature of use	from +5°C up to +25°C
Drying time	approx. 10 h
Technical Approval	IBDIM RT/2011-02-0080/2
In compliance with	PN-B-24620



Available packages:



## IZOHAN epoxy X9

### epoxy-bitumen coat, type E

- **Use:** priming steel and concrete constructions used in sea, river or process water and in corrosive environment after diluting with white spirit in 3:1 ratio paint:spirit; individual protection of concrete objects and steel elements in industry and construction of exposure class XA1, XA2, XA3, as well as ballast and waste water tanks, e.g. in municipal and industrial sewage treatment plants.
- **Properties:** very good adhesion to substrate; forms coating resistant to mechanic load (abrasion, impact); resistant to acid and alkaline sewage waste, sea and industrial water and atmosphere.



Composition	asphalt, epoxy resin, hardener, white spirit
Consumption	0.3 kg/m <sup>2</sup> priming 0.6 kg/m <sup>2</sup> main coat
Mixing ratio	100:34 (comp. A:comp. B)
Recommended no. of coats	2
In compliance with	PN-C-81916





Available packages:



## IZOHAN PRIMING SOLUTION

general-use priming solution, type III

- ▶ **Use:** priming highly absorptive substrates prior to adhesive mortars; protection and reduction of absorptiveness of porous substrates: plasters, concrete, screeds; prevents from too quick drying of adhesive mortars, screeds, fillers and paints; protects concrete surfaces against excessive abrasion and moisture action (can be used in rooms with intensive foot traffic); priming old mineral substrates before application of new coats in order to improve their adhesion (bonding layer).
- ▶ **Properties:** improves surface adhesion and its scratch resistance; regulates the substrate absorption process; strengthens the surface; prevents concrete surfaces from dusting; ecological, friendly to environment and humans.



Composition	dispersion of plastics, additives
Consumption	0,1-0,2 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Technological break between application of subsequent coats	approx. 1 h
In compliance with	PN-C-81906



Available packages:



## IZOHAN EKOLEP

acrylic paste adhesive mortar, D2TE

- ▶ **Use:** fixing polystyrene boards (EPS, XPS) and mineral wool panels to: cement and anhydrite screeds, plasterboards, gypsum plasters, concrete, wood, roofing membranes, bitumen coatings; fixing ceramic tiles onto difficult substrates, tiles on tiles, onto vertical and horizontal surfaces; for indoor and outdoor use.
- ▶ **Properties:** easy in use; watertight; flexible, keeps flexibility in wide range of temperature; sets with no contraction; frost-resistant; does not destroy mineral wool and polystyrene; recommended onto heated floors; ecological – solvent-free.



Composition	dispersion of plastics, additives
Consumption	contact coat: 0,7 kg/m <sup>2</sup> insulation boards fixing: 1,5 kg/m <sup>2</sup> tiles fixing: 1,5-3,7 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Initial shear strength	> 1,0 N/mm <sup>2</sup>
In compliance with	PN-EN-12004



Available packages:



## IZOHAN EKO 1K

one-component waterproofing resistant to negative water pressure, CM, O

- ▶ **Use:** sealing against damp penetrating from the outside (bath-like type); horizontal damp proofing, particularly where it cannot be executed with roll materials (technological breaks in monolithic constructions); sealing external underground building elements subject to groundwater action (also under pressure) in old and contemporary construction; tanks sealing.
- ▶ **Properties:** limits the concrete carbonization process; enables water evaporation from damp constructions; can be tiled directly; resistant to UV rays; resistant to aggressive chemical solutions; resistant to petrol and oils; for indoor and outdoor use; onto vertical and horizontal surfaces; resistant to waste water and pool water; prevents sulfate salts salinity and slightly limits chloride ions penetration.



Composition	dry, modified cement mix
Consumption	approx. 1,5 kg/m <sup>2</sup> /mm coat
Temperature of use	from +8°C up to +30°C
Technological break between application of subsequent coats	approx. 3-4 h
In compliance with	PN-EN-14891



Available packages:



## IZOHAN EKO 2K

two-component flexible waterproofing, CM, O

- ▶ **Use:** sealing buildings of any height, in old and contemporary construction indoors and outdoors; waterproofing terraces and balconies; sealing external basement walls and foundations subject to shrinkage cracks; sealing: swimming pools, slurry tanks, waste water tanks, utility and drinking water tanks, refuse dumps, car washes.
- ▶ **Properties:** limits the concrete carbonization process; enables water evaporation from damp constructions; resistant to aggressive chemical solutions; solvent-free; highly elastic; cracks bridging; resistant to UV rays; resistant to petrol and oils; for indoor and outdoor use.



Composition	water dispersion of plastics, modified cement mix
Consumption	approx. 1,5 kg/m <sup>2</sup> /mm
Temperature of use	from +8°C up to +30°C
Technological break between application of subsequent coats	approx. 3-4 h
In compliance with	PN-EN-14891



Available packages:



## IZOHAN KRYSZTALIZATOR K6

### mineral coating for crystalline sealing

- ▶ **Use:** sealing concrete and ferroconcrete surfaces in industrial, hydrotechnical, sanitary, energetic and general construction; surface sealing and protection of: waste water tanks, drinking water tanks, hydrotechnical objects, swimming pools, foundations and basements; sealing objects subject to positive and negative water pressure; for old as well as contemporary buildings.
- ▶ **Properties:** seals pores in the substrate, forms watertight insulating coating; forms additional subsurface substrate sealing by crystallization of active chemical compounds in the concrete pores; resistant to aggressive environment of exposure class XA3, resistant to chemicals; can be applied onto fresh, wet concrete; can be used on cement plasters, bricks, stone; bridges cracks up to 0.4 mm; resistant to chloride and ozonated water; can be used in drinking water tanks; water vapour permeable.



Composition	portland cement, fine aggregate, chemical additives
Consumption	1.1-1.5 kg/m <sup>2</sup> per coat
Temperature of use	from +15°C up to +20°C
Initial setting time	≥ 60 min.
In compliance with	PN-EN-1504-2(2006)



Available packages:



## IZOHAN ECO-FOIL

### semi-liquid damp proofing foil, DM

- ▶ **Use:** jointless coat sealing in intensively damp rooms prior to ceramic tiles fixing, proofing surfaces easily absorbing damp; for indoor use; can be applied onto any construction material: concrete, plaster, screed, gypsum plaster, plasterboards, floor heating systems.
- ▶ **Properties:** forms jointless coating of high insulating properties; good adhesion to damp proofed surfaces; very elastic and watertight; enables evaporation of water from damp elements; forms perfect insulating underlay beneath ceramic tiles; ecological – solvent-free; dries quickly.



Composition	dispersion of plastics, additives
Consumption	0.4-0.8 kg/m <sup>2</sup> per 2 coats
Temperature of use	from +5°C up to +25°C
Technological break between application of subsequent coats	approx. 4 h
In compliance with	ITB-KOT-2017/0026



Available packages:



## IZOHAN WATERTIGHT BATHROOM

### semi-liquid damp proofing foil

- ▶ **Use:** jointless coat sealing in intensively damp rooms (bathrooms, toilets, laundries, dryers, etc.) prior to ceramic tiles fixing; proofing surfaces easily absorbing damp (e.g. plasterboards, gypsum plasters, gypsum-fibre boards, etc.); for indoor use; can be applied onto any construction material: concrete, plaster, screed, gypsum plaster, plasterboards, with floor heating systems.
- ▶ **Properties:** forms jointless coating of high insulating properties; good adhesion to insulated surfaces; very elastic and watertight; forms perfect insulating underlay beneath ceramic tiles; ecological – solvent-free; dries quickly.



Composition	dispersion of plastics, additives
Consumption	1.0-1.2 kg/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Technological break between application of subsequent coats	approx. 4 h
In compliance with	ITB-KOT-2017/0026



Available packages:



## IZOHAN WATERTIGHT FOUNDATION

### rigid sealing micro-mortar

- ▶ **Use:** indoor sealing against damp penetrating from the outside (bath-like type); sealing outdoor underground building elements subject to groundwater action (also under pressure) in old and contemporary construction; damp proofing in general, communication and hydrotechnical construction; sealing water, waste water, water treatment tanks.
- ▶ **Properties:** limits the concrete carbonization process; enables free water evaporation from damp constructions; resistant to negative and positive water pressure; for indoor and outdoor use on horizontal and vertical surfaces; prevents sulfate salts salinity and slightly limits chloride ions penetration; resistant to waste water and pool water.



Composition	dry modified cement mix
Consumption	approx. 1.5 kg/m <sup>2</sup> /mm
Temperature of use	from +8°C up to +25°C
Technological break between application of subsequent coats	approx. 3-4 h
In compliance with	PN-EN 1504-2

## IZOHAN WATERTIGHT TERRACE

two-component, elastic waterproofing for terraces and balconies, CM, 0



Available packages:



- ▶ **Use:** waterproofing terraces and balconies, can be tiled directly; waterproofing screeds.
- ▶ **Properties:** perfect beneath ceramic cladding; can be applied onto damp substrate; fixing ceramic tiles just after 24 h; solvent-free; elastic, cracks bridging; resistant to UV rays; for outdoor use on horizontal and vertical surfaces.

Composition	water dispersion of plastics, modified cement mix
Consumption	approx. 1.5 kg/m <sup>2</sup> /mm
Temperature of use	from +8°C up to +25°C
Technological break between application of subsequent coats	approx. 3-4 h
In compliance with	PN-EN-14891

## IZOHAN epoxy C-505

epoxy grout, R6



Available packages:



two-component epoxy grout

- ▶ **Use:** grouting ceramic tiles, fittings of whiteware and construction ceramic, gresporcelain and marble, clinker, glass mosaic, natural stone, marble on various substrates. The use of grout IZOCHAN epoxy C-505 is particularly recommended for surfaces requiring high mechanical and chemical resistance, especially in industrial construction.
- ▶ **Properties:** watertight; resistant to low and high temperature; very high mechanical resistance; resistant to chemicals; efficient and easy in use; sets and hardens with no contraction; resistant to abrasion; environment friendly; high filling strength.

Composition	epoxy resin with mineral fillers and additives
Consumption	0,23-2,9 kg/m <sup>2</sup>
Mixing ratio	8:9 component A 1:1 component B
Time of use	approx. 45 minutes
Temperature of use	from +10°C up to +25°C

## IZOHAN epoxy C-506

epoxy grout and adhesive, R6, R2



Available packages:



two-component epoxy grout

- ▶ **Use:** fixing and grouting ceramic tiles, fittings of whiteware and construction ceramic, gresporcelain and marble, clinker, glass mosaic, natural stone, marble on various substrates. The use of grout IZOCHAN epoxy C-506 is particularly recommended where aggressive liquids, brine, mineral or sea water occurs, in breweries, wineries, liquids production plants, distilleries, water treatment plants, laboratories, chemical industry premises, kitchens, dairies, etc., at high pressure and washout, e.g. in industrial washes.
- ▶ **Properties:** watertight; resistant to low and high temperature; very high mechanical resistance; resistant to chemicals; efficient and easy in use; sets and hardens with no contraction; resistant to abrasion; environment friendly; high filling strength.

Composition	epoxy resin with mineral fillers and additives
Consumption for fixing for grouting	1,3 - 2,4 kg/m <sup>2</sup> width [cm] x length [cm] x 1,4 - consumption in g
Mixing ratio	8:9 component A, 1:1 component B
Time of use	approx. 45 minutes
Temperature of use	from +10°C up to +25°C

## IZOHAN adhesive for bitumen membranes and shingles

### single-component roofing adhesive



- ▶ **Use:** gluing bitumen membranes and shingles; repairing cracks in the roofing coatings on all types of roofing.
- ▶ **Properties:** high bonding force; resistant to run-off; immediate grip; resistant to water, UV light or other atmospheric factors; permanently plastic; adhesion to many substrates, also wet [asphalt roofing membranes, any bitumen substrates, concrete, plaster, brick, glass, wood-derived surfaces].

Composition	asphalt, resin, solvent, fibres, additives
Consumption	joint 5x5 mm - approx. 12 linear metre per 300 ml cartridge
Processing temp.	from +5°C to +25°C
Curing time	10-14 days
Bonding capacity	not less than 150 N
Compliance with standard	PN-B-24620

Available product packaging:



## IZOHAN roofing adhesive


### single-component roofing adhesive



- ▶ **Use:** outdoor bonding on horizontal and vertical surfaces of buildings; gluing roofing membranes, shingles and bitumen boards; sealing gaps around flashings, chimneys, hoods, windchests and skylights; fills cavities in the roofing membranes.
- ▶ **Properties:** high bonding force; instant grip; non-corrosive to galvanised sheet metal; resistant to water, UV light or other atmospheric factors; permanently plastic; adhesion to many substrates, also wet [asphalt roofing membranes, any bitumen substrates, concrete, plaster, brick, glass, wood-derived surfaces].

Composition	asphalt, resin, solvent, fibres, additives
Consumption	joint 5x5mm mm - approx. 12 linear metres per 300 ml cartridge
Processing temp.	od +5°C do +25°C
Curing time	10-14 days
Bonding capacity	not less than 150 N
Compliance with standard	PN-B-24620

Available product packaging:



## IZOHAN bitumen roofing sealant

### single-component roofing sealant



- ▶ **Use:** sealing roofing membranes, shingles, sheet metal, roof tiles; sealing around flashing, gaps in roof ducts, gutters, drain pipes, skylights, chimneys, cracks and seams, drains, joints between bituminous materials and metal, wood, stone, and mineral substrates.
- ▶ **Properties:** permanently elastic; very good adhesion to bitumen and mineral substrates; resistant to UV radiation and atmospheric factors; does not run-off; shrink-free bonding; non-corrosive to galvanized sheet metal; does not damage EPS boards; cures under evaporation of the solvent; good adhesion to wet substrates.

Composition	asphalt, dearomatized solvent, fibres, resins, additives
Consumption	joint 5x5 mm - approx. 12 linear metre per 300 ml cartridge
Processing temp.	from -5°C to +25°C
Thermal resistance	from -20°C to +80°C
Curing time	10-14 days
Compliance with standard	PN-B-24620

Available product packaging:



## IZOHAN rubber roofing sealant

### single-component roofing putty type F class 25 HM



- ▶ **Use:** sealing flashings in roofs, deckings, chimneys, and hatches, gutter and drain pipes joints, hole-throughs in roofs and deckings; repair of roofs covered with bitumen roofing membrane, areas around skylights and roof windows, corrugated or trapezoidal sheet metal joints, asbestos-cement boards, bitumen boards.
- ▶ **Properties:** highly elastic joint; resistant to aging, UV radiation and atmospheric factors; paintable; can be applied on damp substrates; very good adhesion to most materials used in construction industry (membranes, bitumen, steel, ceramics, stone, wood, glass)
- ▶ **Available colours:** colourless, brown

Composition	rubber, resin, plasticiser, organic solvent,
Consumption	depending on demand
Processing temp.	from +5°C to +25°C
Drying time	2 mm/24h [20°C, 65% relative humidity]
Thermal resistance after curing	from -20°C to +80°C
Compliance with standard	PN-EN ISO 11600

Available product packaging:







Available product packaging:




## IZOHAN roofing putty asphalt-rubber roofing mix

- ▶ **Use:** sealing flashings, gaps in roof ducts, gutters, drain pipes, skylights, chimneys, cracks and seams, joints between bituminous materials and metals, mineral substrates and stone; repair of roofs.
- ▶ **Properties:** resistance to: weather conditions, run-off, shrinkage cracks; non-corrosive to galvanized sheet metal; cures under evaporation of the solvent; very good adhesion to the substrate.



Composition	asphalt, resin, rubber, fibres, additives
Consumption	joint 5x5 mm - approx. 12 linear metre per 300 ml cartridge
Application and bonding:	from +5°C to +25°C
Curing time	10-14 days
Compliance with standard	PN-B-24620



Available packages:



## IZOHAN IZO-DEKOR protective and decorative coating

- ▶ **Use:** eco protective and decorative coating intended for restoration and protection of objects and structures made of concrete, wood or turf and roofing made of bitumen shingles, ceramic roofing tiles, eternit, bitumen membranes, metal roofing tiles, galvanised sheet metal, tar.
- ▶ **Properties:** waterproof; resistant to reemulsification; durable and frostproof; resistant to dry friction; quick and easy for use [ready-to-use]; very good coverage properties; resistant to atmospheric factors [so-called acid rain, UV light]; very good adhesion to the substrate, detachment is only possible with simultaneous damage of the substrate; resistant to lye, acid-resistant and resistant to water, soapy water and scrubbing.
- ▶ **Available colours:** green, red, brown, black, grey [other per request]



Composition	dispersion plastics, additives, pigment
Consumption	approx. 0.4-0.5 kg/m <sup>2</sup> per coating
Processing temp.	from +5°C to +25°C
Processing temp.	approx. 4 h



Available packages:



## IZOHAN impregnant IPC impregnant for ceramic substrates

- ▶ **Use:** impregnation of any ceramic surfaces, particularly roofing tiles and bricks as well as ceramic tiles, terracotta, natural stone, sandstone, gypsum; used where aesthetics as well as resistance of impregnated surfaces to soiling or atmospheric conditions required.
- ▶ **Properties:** strengthens and hydrophobizes mineral construction materials and sand; penetrates deeply, dries quickly, gives perfect long term hydrophobization result, even after substantial dilution; forms vapour-permeable and colourless coating; perfectly reduces absorption of water and dissolved salts (e.g. chlorides); significantly reduces white efflorescence on the surface; resistant to alkaline environment; can be used as a binder for silicate-based paints.



Composition	silicone-silicate concentrate, approx. 60% of active components, water dilutable, contains no VOC
Penetration depth	5-8 mm
Consumption	approx. 0.3-0.4 l/m <sup>2</sup>
Temperature of use and storage	from +5°C up to +30°C
Water absorption after 24 h after application	max. 1%



Available packages:



## IZOHAN impregnant W2 impregnant for wood, O, Gp

- ▶ **Use:** protection of wooden elements against wood pests (insects); protection against growth of fungi destroying wood – Coniophora puteana, causing blue stains – Aureo-basidium pullulans, Scierophoma pithyophila, causing surface mould – Cladosporium sphaerospermum, Aspergillus niger, Penicillium funiculosum.
- ▶ **Properties:** efficiently protects wooden construction elements against mould, fungi destroying the structure as well as insects; very good preserving properties; easy and quick in use; application can be done independently, no special equipment required; spray-applied or applied with a paint brush; forms colourless protecting coating resistant to changeable weather conditions.



Composition	chloroparaffin, linseed oil, organic solvent, mix of zinc octanoate, tolylfuaniid, cypermethrine
Consumption	approx. 0.33 l/m <sup>2</sup> when used 2-3 times 27 m <sup>2</sup> of wood
Temperature of use	from +5°C up to +25°C
Consistency	oily
In compliance with	PN-E-04906

## IZOHAN PAVEMENT GUARD

### impregnant for sett



Available packages:



- ▶ **Use:** impregnation and sealing substrates made of sett where aesthetics as well as resistance to any stains and atmospheric conditions are required. Particularly recommended for surfaces close to houses, shops, petrol stations, pedestrian and vehicle routes; the preparation should not be used on surfaces made of clinker brick. It is advisable to perform a test on facings made of lime, sandstone and other natural stone.
- ▶ **Properties:** improves the surface appearance; limits abrasiveness; strengthens the colour; protects the surface against durable stains of oil and other contaminants (but does not clean the existing ones); improves the surface resistance against atmospheric conditions (frost, rain); available in two versions: semi-matt and gloss.

Composition	synthetic resins, organic solvents, additives
Consumption	0,17-0,2 l/m <sup>2</sup>
Temperature of use	from +5°C up to +25°C
Drying time	2 h
Technical approval	IBDIM AT/2005-03-1876/2
Available versions	semi-matt and gloss

## IZOHAN epoxy P-405

### epoxy paint, B



Available packages:  
2-component epoxy paint



- ▶ **Use:** IZOCHAN epoxy P-405 can be used outdoors, e.g. on balconies and indoors: in residential, public access buildings, garages, industrial halls, storage rooms, warehouses, including the food industry facilities, e.g. dairies, butcheries, bakeries, breweries, etc.
- ▶ **Properties:** forms durable coating resistant to mechanical factors and well adhering to the substrate; resistant to point and prolonged loads; resistant to high temperature (up to approx. 120°C), water action, cleaning agents, disinfectants and chemicals; resistant to damage caused by car tires; very good coating properties.

Composition	epoxy resin, hardener, additives
Consumption	0,2-0,4 kg/m <sup>2</sup>
Temperature of use	from +8°C up to +25°C
Drying time	up to 24 h (grade 6)
In compliance with	PN-C-81916

- ▶ **Basic colours:** light grey, dark grey, graphite, light green, sea blue, dark green, beige (ivory), brick-red, light blue, dark blue

## IZOHAN epoxy EP-601

### epoxy primer, B



Available packages:



- ▶ **Use:** for priming mineral and steel substrates prior to application of epoxy membrane IZOCHAN epoxy EP-602; for strengthening absorbable, porous substrates and/or those of poor mechanical strength; as a contact coat on grinded ceramic cladding, stone, terrazzo, steel surfaces; as a primer beneath heat-welded membranes on damp substrates (fresh concrete from 3 up to 14 days).
- ▶ **Properties:** very good adhesion to the substrate; strengthens the primed substrate; resistant to chemicals of acid and alkaline reaction, water action, sea and industrial atmosphere, frost-resistant; can be applied on very damp substrates; short setting time also on damp substrates.

Composition	epoxy resin, hardener
Drying time	0,2-0,5 kg/m <sup>2</sup>
Time between the application of individual layers	24 h
Temperature of use	from +15°C up to +30°C
In compliance with	PN-C-81911
Technical approval	IBDIM AT/2015-02-3116

## IZOHAN epoxy EP-602

### epoxy membrane, C



Available packages:



- ▶ **Use:** for independent protection of concrete construction and steel elements in industry and general construction, ballast and waste water tanks, e.g. in domestic and industrial waste water treatment plants, inland and sea hydrotechnical construction; in version with sand forms a surface coat protecting the pedestrian routes and routes loaded with vehicles traffic (e.g. multi-position garages), on terraces and balconies as surface waterproofing.
- ▶ **Properties:** very good adhesion to the substrate; forms coating resistant to mechanical loads (abrasion, impact); resistant to chemicals of acid and alkaline reaction, water action, sea and industrial atmosphere, oils, petrol, etc.; after mixing with quartz sand forms ductile-flexible waterproofing and top finish of high abrasion resistance.

Composition	epoxy resin, filler, pigment, additives, hardener
Drying time	1,0-4,0 kg/m <sup>2</sup>
Time between the application of individual layers	24 h
Resistance to peeling off the concrete substrate	min. 2,0 MPa
In compliance with	PN-C-81916
Technical approval	IBDIM AT/2015-02-3116

## IZOLEX DYSPERBIT PRIMER

### anionic asphalt-latex emulsion



Available packages:



- ▶ **Use:** primer for bitumen water-diluted compounds and solvent-based coatings, weldable roofing membranes.
- ▶ **Properties:** can be used both on dry or wet substrates; due to added resins strongly binds to the substrate; safe in direct contact with polystyrene.



Composition	water anionic dispersion modified with rubber, asphalts and resins
Consumption	primer for: coatings [dilution with water at 1:9 ratio]: 0.15-0.3 l of solution /m <sup>2</sup> /layer; weldable roofing membranes [at a dilution of 1:4] of solution /m <sup>2</sup> /layer
Processing temp.	from +5°C to +35°C
Coating development time	approx. 3 h
Compliance with standard	PN-B-24002

## IZOLEX DYSPERBIT Dn

### asphalt-natural rubber dispersion compound



Available packages:



- ▶ **Use:** seam-free damp-proof courses on underground and ground parts of the buildings; priming substrates after dilution with water; restoration and maintenance of asphalt roofing materials; performance of reinforced jointless roofing.
- ▶ **Properties:** contains high quality chemical additives to improve application properties adhesion and elasticity; safe in direct contact with polystyrene; to be applied on dry or slightly damp substrate.



Composition	water dispersion of asphalts, fillers, rubbers, and performance additives
Consumption	0.5-1.0 kg/m <sup>2</sup> /layer
Processing temp.	from +5°C to +30°C
Coating development time	no later than after 6 hours have elapsed
Compliance with standard	PN-B-24000

## IZOLEX STYRBIT 2000

### asphalt-rubber dispersion compound



Available packages:



- ▶ **Use:** seam-free, elastic damp-proof and water-proof coatings [medium type] on underground and ground parts of the building; adhering thermal insulation EPS, XPS, and PIR boards.
- ▶ **Properties:** ready-to-use; solvents-free; can be applied also on substrates with complicated shapes and any slope; highly-modified with rubber; safe in direct contact with polystyrene foam.



Composition	water dispersion of asphalts, fillers, rubbers, and performance additives
Consumption	approx. 1.5 kg/m <sup>2</sup> /1 mm dry residue; 1.2-2.0 kg EPS adhesion
Processing temp.	from +5°C to +30°C
Coating development time	not more than 6 hours
Drying time	3-5 days, bonding time as an adhesive 10-15 days
Resistance to rain	not more than 6 hours
Technical Approval	AT/2016-02-3259
Compliance with standard	PN-B-24000

## IZOLEX HYDROLEX 2E

### bitumen, two-component, thick-layer asphalt coating modified with polymer



Available packages:



- ▶ **Use:** seam-free elastic waterproof coatings on vertical or horizontal underground or ground parts of the building, i.e. foundation walls, boards, foundation feet; bonding thermal insulation boards and drainage slabs; underfloor insulation in basements and garages.
- ▶ **Properties:** high application properties; good adhesion and elasticity; bridges cracks; safe in contact with EPS and XPS boards; should be used from the side where damp or water pressure occurs.



Composition	water dispersion of bitumen and rubber, mineral filler
Resistance to rain	after approx. 2 h
Consumption	waterproofing approx. 13 kg/m <sup>2</sup> ; bonding 1.0-2.0 kg /m <sup>2</sup>
Accuracy for pressurized water	0.8 MPa
Processing temp.	from +5°C to +30°C
Compliance with standard	PN-EN 15814



Available packages:



## IZOLEX HYDROLEX 2E Styro

two-component, thick-layer asphalt coating with polystyrene filling

- ▶ **Use:** performing seam-free waterproof coatings on vertical or horizontal underground or ground parts of the building; bonding thermal insulation boards and drainage slabs; underfloor insulation in basements and garages.
- ▶ **Properties:** forms a fast drying, elastic coating for scratch bridging; resistant to rain after approx. 3 hours; manual application or by spray method; solvents-free; resistant to aggressive substances contained in the primer; safe in contact with EPS and XPS boards.



Composition	water dispersion of bitumen and rubber, polystyrene filling, mineral filler
Consumption	1,1-1,3 l/m <sup>2</sup> /mm
Full cure	within approx. 2 days
Coating formation time / resistance to rain	after approx. 5 h after approx. 3 h
Processing temp	from +5°C to +30°C
Working time	approximately 1-2 h after mixing
Compliance with standard	PN-EN 15814



Available packages:



## IZOLEX ARBOLEX-AQUA STOP

roofing putty for repair and sealing

- ▶ **Use:** repairing defects and gaps, fillings in roofing [kinks, cracks, gaps, blisters, leaks, etc.]; local waterproofing sealing; sealing technical passages.
- ▶ **Properties:** safe in contact with XPS and EPS boards; does not require priming; can be used on frozen substrates in freezing temperatures down to -20°C; can be applied on dry, damp or wet substrates; resistant to aggressive substances contained in the primer



Composition	asphalt, dearomatized solvents, performance additives
Consumption	approx. 1.2 kg / 1 mm <sup>2</sup>
Substrate and ambient temperature during application and setting	from +5°C to +35°C
Drying time	no staining after 3-5 h, completely dry after 35 days
Compliance with standard	PN-B-24620



Available packages:



## IZOLEX STYRBIT 2000-K

asphalt-rubber compound

- ▶ **Use:** bonding layered boards [polystyrene roofing membrane], polystyrene boards, mineral wool or other insulating materials to concrete, bitumen [also roofing membrane], trapezoidal metal sheet, etc.; bonding roofing membrane to membrane; waterproofing underground and ground parts of the buildings.
- ▶ **Properties:** can be applied on slightly damp substrates; resistant to weak acids and alkalis; may be used in contact with polystyrene type XPS, EPS.



Composition	asphalt, dearomatized solvents, SBS, and other performance additives
Consumption	waterproofing 0,6-1,2 kg / m <sup>2</sup> ; bonding 0,8-2,0 kg / m <sup>2</sup>
Substrate and ambient temperature during application and setting:	from +5°C to +35°C
Layer drying time	no staining after 6 h, completely dry after 24 h; full strength as an adhesive 14 days
Technical Recommendation	AT IBDIM nr AT/2016-02-3259
Compliance with standard	PN-B-24620



Available packages:



## IZOLEX IZOBIT Br

asphalt-rubber priming solution

- ▶ **Use:** primer for solvent-based coating waterproofing and weldable roofing membranes; waterproofing underground and ground parts of the buildings; applied on: concrete, brick, sheet metal, roofing membranes, and other bituminous substrates, fibre cement.
- ▶ **Properties:** deeply penetrates the substrate; very good adhesion to the substrate; resistant to aggressive substances contained in the primer; highly elastic; can be used on dry or wet substrates.



Composition	mixture of asphalts, solvents, and performance additives
Consumption	0,5-0,3 kg/m <sup>2</sup>
Processing temp.	from +5°C to +35°C
Drying time	not more than 12 h
Technical Approval	AT/2016-02-3252
Compliance with standard	PN-B-24620





Available packages:



## IZOLEX IZOBIT Dk asphalt and rubber resin-modified compound

- ▶ **Use:** maintenance of roofing made of roofing membranes, bitumen shingles, metal sheet, fibre cement; seam-free damp-proof coatings on underground parts of the building as laminates reinforced with technical fabrics.
- ▶ **Properties:** resistant to aggressive substances contained in the primer; high resistance to UV light; shows excellent plasticity, also at subzero temperatures.



Composition	mixture of asphalts, solvents, and performance additives
Consumption	0.5-0.9 kg/m <sup>2</sup>
Processing temp.	from +5°C to +35°C
Drying time	no staining after 6 h, completely dry after 24 days
Compliance with standard	PN-B-24620

**IZOLEX**



Available packages:



## IZOLEX COLD-APPLIED BINDER asphalt-resin binder

- ▶ **Use:** adhering bitumen roofing membranes to substrates; bonding layers of the roofing membrane, forming jointless waterproofing coatings in ground and underground parts of the building.
- ▶ **Properties:** strong binding to the substrate; resistant to weak acids and alkalis, and UV light.



Composition	mixture of asphalts, solvents, fillers, and performance additives
Consumption	0.5-1.0 kg/m <sup>2</sup>
Processing temp.	from +5°C to +35°C
Drying time	no staining after 6 h, completely dry after 24 h bonding time as an adhesive 14-15 days
Compliance with standard	PN-B-24620



Available packages:




## IZOLEX IZOBIT ALU asphalt-resin binder

- ▶ **Use:** insulating and decorating coating in silver, reflecting sunlight and sealing microcracks; for roofing membranes, bitumen shingles, fibre cement, galvanised metal sheet, bituminous coatings and concrete walls and mineral plaster.
- ▶ **Properties:** coating in silver of a decorative value, reflects sunlight to prevent heating of the surface and rooms below; resistant to weather conditions and weak acids and alkalis; significantly extends the lifespan of roofing, very good adhesion to the substrate.



Composition	mixture of asphalts, polymers and the aluminium pigment in the form of flakes
Consumption	0.10-0.25 kg/m <sup>2</sup>
Processing temp.	from +5°C to +35°C
Drying time	no staining after 6 h, completely dry after 12 days
Thickness of a single layer	0.1-0.25 mm
Compliance with standard	PN-B-24004

**solvent-based bitumens**



## IZOLMAT PLAN monomax®

highly SBS-modified heat-welded top layer bitumen membrane

► **Use:** highly SBS-modified bitumen membrane for single layer proofing of flat roofs on thermal insulation EPS, XPS, PIR boards, mineral wool or concrete. IZOLMAT PLAN monomax is a roll membrane, with SBS-modified asphalt with polyester and fiberglass reinforcing. Membrane has a wide, granules-free overlapping strip (approx. 11 cm) ensuring a single layer roofing membrane. Can be installed on wooden substrates on a protective layer made of non-weldable membranes.

► **Granules type:**  steel



Roll dimensions (m)	5 x 1	
Thickness (mm)	5,2	
Reinforcement	polyester reinforced with fiberglass fabric	
Asphalt type, cold flexibility [°C]	mod. SBS, -25	
Flow resistance [°C]	+100 ± 10	
Tensile strength	longitudinal	transversal
	1200 ± 300 (N/5 cm)	850 ± 250 (N/5 cm)
Elongation	50 ± 15 (%)	50 ± 15 (%)
	Fire rate	
B <sub>ros</sub> (t), B <sub>ros</sub> (t)/NRO, REI		

## IZOLMAT PLAN protection®

PYE PV250 S5,2 SS

highly SBS-modified heat-welded top layer bitumen membrane



► **Use:** highly SBS-modified heat-welded top layer bitumen membrane with additive retarding fire spreading. For use as a second membrane layer on newly constructed roofs or as a single layer membrane for roofing repairs. Product manufactured with polyester reinforcement, provides safe and durable membrane.

► **Granules type:**  anthracite



Roll dimensions (m)	5 x 1	
Thickness (mm)	5,2	
Reinforcement	polyester	
Asphalt type, cold flexibility [°C]	mod. SBS, -25	
Flow resistance [°C]	+100 ± 10	
Tensile strength	longitudinal	transversal
	1100 ± 200 (N/5 cm)	900 ± 200 (N/5 cm)
Elongation	50 ± 10 (%)	50 ± 10 (%)
	Fire rate	
B <sub>ros</sub> (t), B <sub>ros</sub> (t)/NRO, REI		

## IZOLMAT PLAN PYE PV250 S5,2 SS

highly SBS-modified heat-welded top layer bitumen membrane



► **Use:** highly SBS-modified heat-welded top layer bitumen membrane for roofs of any substrate type. For use as a second membrane layer on newly constructed roofs or as a single layer membrane for roofing repairs. Product manufactured with polyester reinforcement, provides safe and durable membrane. Typical high-quality heat-welded membrane used on large and small size roofs.

► **Granules type:**  steel  red  green  
 autumn brown



Roll dimensions (m)	5 x 1	
Thickness (mm)	5,2	
Reinforcement	polyester	
Asphalt type, cold flexibility [°C]	SBS mod, -25°C	
Flow resistance [°C]	+100	
Tensile strength	longitudinal	transversal
	1200 ± 250 (N/5 cm)	900 ± 250 (N/5 cm)
Elongation	50 ± 15 (%)	50 ± 15 (%)
	Fire rate	
B <sub>ros</sub> (t), B <sub>ros</sub> (t), B <sub>ros</sub> (t)/NRO, REI		

## IZOLMAT PLAN extra PYE PV200 S5,2 SS

highly SBS-modified heat-welded top layer bitumen membrane



- ▶ **Use:** highly SBS-modified heat-welded top layer bitumen membrane for roofs of any substrate type and dimensions. Used as a membrane in two-layer systems on newly constructed roofs or as a single layer membrane for roofing repairs.

- ▶ **Granules type:**  steel

Roll dimensions (m)	5 x 1	
Thickness (mm)	5,2	
Reinforcement	polyester	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
Flow resistance (°C)	+100 ± 10	
	longitudinal	transversal
Tensile strength	1000 ± 150 (N/5 cm)	750 ± 150 (N/5 cm)
Elongation	50 ± 15 (%)	50 ± 15 (%)
Fire rate	B <sub>roof</sub> (t), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	



IZOLMAT

## IZOLMAT PLAN PYE PV200 S4,2 SS

highly SBS-modified heat-welded top layer bitumen membrane



- ▶ **Use:** highly SBS-modified heat-welded top layer bitumen membrane for roofs of any substrate type and dimensions. Used as a membrane in two-layer systems on newly constructed roofs or as a single layer membrane for roofing repairs.

- ▶ **Granules type:**  steel

Roll dimensions (m)	5 x 1	
Thickness (mm)	4,2	
Reinforcement	polyester	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
Flow resistance (°C)	+100 ± 10	
	longitudinal	transversal
Tensile strength	850 ± 150 (N/5 cm)	550 ± 150 (N/5 cm)
Elongation	50 ± 10 (%)	50 ± 10 (%)
Fire rate	B <sub>roof</sub> (t), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	



## IZOLMAT opti 20 PYE PV250 S5,2 SS

highly SBS-modified heat-welded top layer bitumen membrane



- ▶ **Use:** highly SBS-modified heat-welded top layer bitumen membrane. Used as a membrane in single-layer systems as well as in multi-layer systems with underlayer membrane or renovated roofing membranes. For heat-welding or mechanical fixing. Particularly recommended for roof flashings and at zones of intensive thermal and dynamic roof movements.

- ▶ **Granules type:**  steel

Roll dimensions (m)	5 x 1	
Thickness (mm)	5,2	
Reinforcement	polyester reinforced with fiberglass fabric	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
Flow resistance (°C)	+100 ± 10	
	longitudinal	transversal
Tensile strength	750 ± 200 (N/5 cm)	450 ± 200 (N/5 cm)
Elongation	45 ± 15 (%)	45 ± 15 (%)
Fire rate	B <sub>roof</sub> (t), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	



heat-welded top layer bitumen membranes



## IZOLMAT BIT V60 S4,2 SS

### unmodified heat-welded top layer bitumen membrane



► **Use:** unmodified heat-welded top layer bitumen membrane for small size roofs and concrete substrate. Requires an underlayer membrane or repaired old roofing layers. Membrane is not used for roof details working.

► **Granules type:**  steel

Roll dimensions (m)	5 x 1	
Thickness (mm)	4,2	
Reinforcement	glass veil	
Asphalt type, cold flexibility [°C]	oxidised, 0	
Flow resistance [°C]	+80 ± 10	
	longitudinal	transversal
Tensile strength	500 ± 200	300 ± 150 (N/5 cm)
Elongation	4 ± 2 [%]	4 ± 2 [%]
Fire rate	B <sub>ros(t)</sub> /NR0, REI	

## IZOLMAT PLAN PYE PV250 S5,0

### highly SBS-modified heat-welded underlayer bitumen membrane



► **Use:** highly SBS-modified heat-welded underlayer bitumen membrane for balconies, terraces and foundations. With strong polyester reinforcement, with high elasticity and tensility. As an underlayer membrane with no limitations of use.

► **Granules type:**  fine grain



Roll dimensions (m)	5 x 1	
Thickness (mm)	4,8	
Reinforcement	polyester	
Asphalt type, cold flexibility [°C]	mod. SBS, -20	
	longitudinal	transversal
Tensile strength	1050 ± 150 (N/5 cm)	850 ± 250 (N/5 cm)
Elongation	50 ± 10 [%]	50 ± 10 [%]
Fire rate	B <sub>ros(t)</sub> , B <sub>ros(t)</sub> /NR0, REI	

## IZOLMAT PLAN PYE G200 S4,0

### highly SBS-modified heat-welded underlayer bitumen membrane



► **Use:** highly SBS-modified heat-welded underlayer membrane for mechanical fastening on roofs and for terraces and foundations proofing. With fiberglass reinforcement and high tensile strength.

► **Granules type:**  fine grain



Roll dimensions (m)	5 x 1	
Thickness (mm)	4,0	
Reinforcement	fiberglass	
Asphalt type, cold flexibility [°C]	mod. SBS, -20°C	
	longitudinal	transversal
Tensile strength	1500 ± 500 (N/5 cm)	2900 ± 900 (N/5 cm)
Elongation	12 ± 7 [%]	12 ± 7 [%]
Fire rate	B <sub>ros(t)</sub> , B <sub>ros(t)</sub> /NR0, REI	

## IZOLMAT PLAN PYE PV180 S4,0

### SBS-modified heat-welded underlayer bitumen membrane



► **Use:** SBS-modified heat-welded underlayer membrane for terraces, balconies and foundations as well as the first roofing membrane layer. With strong polyester reinforcement of high elasticity and tensility, can be used for mechanical fastening.

► **Granules type:**  fine grain



Roll dimensions (m)	7,5 x 1	
Thickness (mm)	4,0	
Reinforcement	polyester	
Asphalt type, cold flexibility [°C]	mod. SBS, -15	
	longitudinal	transversal
Tensile strength	850 ± 150 (N/5 cm)	550 ± 150 (N/5 cm)
Elongation	50 ± 10 [%]	50 ± 10 [%]
Fire rate	B <sub>ros(t)</sub> , B <sub>ros(t)</sub> /NR0, REI	




## IZOLMAT PLAN ultimax

### low-SBS-modified heat-welded underlayer bitumen membrane



► **Use:** SBS-modified heat-welded underlayer membrane with fiberglass reinforcement used as the first roofing membrane layer, also for mechanical fastening. Instead of fine granules the membrane is top coated with easily fusible non-woven fabric accelerating the welding of the subsequent membrane layer.

► **Top coat:**  non-woven fabric



Roll dimensions (m)	10 x 1	
Thickness (mm)	2.5	
Reinforcement	fiberglass	
Asphalt type, cold flexibility (°C)	mod. SBS, -5	
	longitudinal	transversal
Tensile strength	1500 ± 500 (N/5 cm)	2800 ± 800 (N/5 cm)
Elongation	6 ± 3 (%)	6 ± 3 (%)
Fire rate	B <sub>roof</sub> (t <sub>1</sub> ), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	


## IZOLMAT PLAN ultimax SBS

### SBS-modified heat-welded underlayer bitumen membrane



► **Use:** SBS-modified heat-welded underlayer bitumen membrane with fiberglass reinforcement used as the first roofing membrane layer. Used also as damp- and waterproofing of underground building elements (type A and T). Instead of fine granules the membrane is top coated with easily fusible non-woven fabric accelerating the welding of the subsequent membrane layer. The modification of asphalt used in the membrane allows to use the product in low ambient temperature. For heat-welding and mechanical fastening.

► **Top coat:**  non-woven fabric



Roll dimensions (m)	10 x 1	
Thickness (mm)	2.5	
Reinforcement	fiberglass	
Asphalt type, cold flexibility (°C)	mod. SBS, -15	
	longitudinal	transversal
Tensile strength	1500 ± 500 (N/5 cm)	2900 ± 900 (N/5 cm)
Elongation	8 ± 4 (%)	8 ± 4 (%)
Fire rate	B <sub>roof</sub> (t <sub>1</sub> ), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	

## IZOLMAT PLAN PYE


### PV160 S3,0

#### SBS-modified heat-welded underlayer bitumen membrane



► **Use:** SBS-modified heat-welded underlayer bitumen membrane for terraces, balconies and foundations, also used as the first roofing membrane layer. With strong polyester reinforcement of high elasticity and tensility, can be used for mechanical fastening.

► **Granules type:**  fine grain



Roll dimensions (m)	7.5 x 1	
Thickness (mm)	3.0	
Reinforcement	polyester	
Asphalt type, cold flexibility (°C)	mod. SBS, -15	
	longitudinal	transversal
Tensile strength	750 ± 150 (N/5 cm)	500 ± 150 (N/5 cm)
Elongation	45 ± 15 (%)	45 ± 15 (%)
Fire rate	B <sub>roof</sub> (t <sub>1</sub> ), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	

## IZOLMAT opti 20 PYE


### PV200 S4,0

#### highly SBS-modified heat-welded underlayer bitumen membrane



► **Use:** highly SBS-modified heat-welded underlayer bitumen membrane used for roof waterproofing as well as damp- and waterproofing of underground building elements (type A and T). Enables to form systems meeting the B<sub>roof</sub>(t<sub>1</sub>), B<sub>roof</sub>(t<sub>2</sub>) class. For heat-welding and mechanical fastening.

► **Granules type:**  fine grain



Roll dimensions (m)	7.5 x 1	
Thickness (mm)	4.0	
Reinforcement	polyester	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
	longitudinal	transversal
Tensile strength	850 ± 250 (N/5 cm)	650 ± 300 (N/5 cm)
Elongation	50 ± 15 (%)	50 ± 15 (%)
Fire rate	B <sub>roof</sub> (t <sub>1</sub> ), B <sub>roof</sub> (t <sub>2</sub> )/NRO, REI	

## IZOLMAT opti 5 PYE PV200 S4,0

low-SBS-modified heat-welded underlayer bitumen membrane



► Use: low-SBS-modified heat-welded underlayer bitumen membrane used for roof waterproofing as well as damp- and waterproofing of underground building elements (type A and T). Enables to form systems meeting the  $B_{roof}(t_e)$ ,  $B_{roof}(t_e)$  class. For heat-welding and mechanical fastening.

► Granules type:  fine grain



Roll dimensions (m)	7,5 x 1	
Thickness (mm)	4,0	
Reinforcement	polyester	
Asphalt type, cold flexibility (°C)	mod. SBS, -5	
	longitudinal	transversal
Tensile strength	850 ± 250 (N/5 cm)	650 ± 300 (N/5 cm)
Elongation	50 ± 15 (%)	50 ± 15 (%)
Fire rate	$B_{roof}(t_e)$ , $B_{roof}(t_e)$ /NRO, REI	

## IZOLMAT opti 5 PYE G200 S4,0

low-SBS-modified heat-welded underlayer bitumen membrane



► Use: modified heat-welded underlayer bitumen membrane with addition of SBS used as damp-proofing of underground building elements (type A). Used also as an underlayer membrane in two-layer roofing systems. For heat-welding and mechanical fastening.

► Granules type:  fine grain



Roll dimensions (m)	7,5 x 1	
Thickness (mm)	4,0	
Reinforcement	fiberglass	
Asphalt type, cold flexibility (°C)	mod. SBS, -5	
	longitudinal	transversal
Tensile strength	1500 ± 500 (N/5 cm)	2800 ± 800 (N/5 cm)
Elongation	6 ± 3 (%)	6 ± 3 (%)
Fire rate	$B_{roof}(t_e)$ , $B_{roof}(t_e)$ /NRO, REI	

## IZOLMAT BIT G200 S4,0

unmodified heat-welded underlayer bitumen membrane



► Use: unmodified heat-welded underlayer bitumen membrane for mechanical fastening on thermal insulation and for water vapour barriers on sheet and concrete substrates. Used also as damp-proofing of underground building elements (type A). Can be used in periods of temperature above +5°C within whole day and night time.

► Granules type:  fine grain



Roll dimensions (m)	5 x 1	
Thickness (mm)	4,0	
Reinforcement	fiberglass	
Asphalt type, cold flexibility (°C)	oxidated, 0	
	longitudinal	transversal
Tensile strength	1500 ± 500 (N/5 cm)	2800 ± 800 (N/5 cm)
Elongation	6 ± 3 (%)	6 ± 3 (%)
Fire rate	$B_{roof}(t_e)$ , $B_{roof}(t_e)$ /NRO, REI	

## IZOLMAT BIT V60 S4,0

unmodified heat-welded underlayer bitumen membrane



► Use: unmodified heat-welded underlayer bitumen membrane with fiberglass reinforcement. Used as the first layer on roof concrete substrates or as water vapour barrier beneath thermal insulation on concrete substrates.

► Granules type:  fine grain



Roll dimensions (m)	5 x 1	
Thickness (mm)	4,0	
Reinforcement	glass veil	
Asphalt type, cold flexibility (°C)	oxidated, 0	
	longitudinal	transversal
Tensile strength	500 ± 200 (N/5 cm)	300 ± 150 (N/5 cm)
Elongation	4 ± 2 (%)	4 ± 2 (%)
Fire rate	$B_{roof}(t_e)$ /NRO, REI	

## IZOLMAT BIT V60 S3,0

### unmodified heat-welded underlayer bitumen membrane



- ▶ **Use:** unmodified heat-welded underlayer bitumen membrane with fiberglass fabric reinforcement. Used as the first layer on roof concrete substrates or as water vapour barrier beneath thermal insulation on concrete substrates.

- ▶ **Granules type:**  fine grain



Roll dimensions (m)	7,5 x 1	
Thickness (mm)	3,0	
Reinforcement	glass veil	
Asphalt type, cold flexibility (°C)	oxidated, 0	
	longitudinal	transversal
Tensile strength	500 ± 200 (N/5 cm)	300 ± 150 (N/5 cm)
Elongation	4 ± 2 (%)	4 ± 2 (%)
Fire rate	B <sub>vor</sub> (t)/NRO, REI	

IZOLMAT

## IZOLMAT TOP SP

### highly SBS-modified self-adhesive top layer bitumen membrane



- ▶ **Use:** highly SBS-modified self-adhesive top layer bitumen membrane for any substrate type, including the wooden and wood-based one. Fixed onto underlayer membrane or old renovated roofing membrane. Can be mechanically fastened. Recommended for zones where open flame must not be used. Performing flashings according to the product technical data sheet guidelines.

- ▶ **Granules type:**  steel



Roll dimensions (m)	5 x 1	
Thickness (mm)	4,2	
Reinforcement	polyester reinforced with fiberglass fabric	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
Flow resistance (°C)	+100 ± 10	
	longitudinal	transversal
Tensile strength	1000 ± 250 (N/5 cm)	750 ± 250 (N/5 cm)
Elongation	50 ± 15 (%)	50 ± 15 (%)
Fire rate	B <sub>vor</sub> (t)/ NRO, REI	

## IZOLPLAN PYE G200 S3,0 SP

### highly SBS-modified self-adhesive underlayer bitumen membrane



- ▶ **Use:** highly SBS-modified self-adhesive underlayer bitumen membrane used on thermal insulation boards on roofs and terraces. Can be mechanically fastened to mineral wool panels. Top coated with foil. Performing flashings according to the product technical data sheet guidelines.

- ▶ **Top coat:**  foil



Roll dimensions (m)	10 x 1	
Thickness (mm)	3,0	
Reinforcement	fiberglass	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
Tensile strength	longitudinal	transversal
	1500 ± 500 (N/5 cm)	2900 ± 900 (N/5 cm)
Elongation	12 ± 7 (%)	12 ± 7 (%)
Fire rate	B <sub>vor</sub> (t), B <sub>vor</sub> (t), B <sub>vor</sub> (t)/NRO, REI	

## IZOLMAT PLAN green roof PYE PV250 S5,0

### highly SBS-modified heat-welded bitumen membrane



- ▶ **Use:** highly SBS-modified heat-welded bitumen membrane with additive limiting the roots growth, manufactured with polyester reinforcement. Used on green roofs as the second sealing and roots blocking layer. Prolonged membrane durability resulting from greater thickness and stronger reinforcement.

- ▶ **Granules type:**  coarse grain



Roll dimensions (m)	5,5 x 1	
Thickness (mm)	5,0	
Reinforcement	polyester	
Asphalt type, cold flexibility (°C)	mod. SBS, -20	
Tensile strength	longitudinal	transversal
	1100 ± 150 (N/5 cm)	900 ± 200 (N/5 cm)
Elongation	50 ± 10 (%)	50 ± 10 (%)

special application bitumen membranes